



Military-Fasteners.com

P/N NAS428H4A7

Description

Fastener Length: 7/8", Hole Diameter: ", Thread: 1/4-28, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS428H4A7 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5306-01-527-5479 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS428H4A7 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.000 Inches Minimum And 1.062 Inches Maximum |
| Fastener Length: | 0.875 Inches Nominal |
| Head Style: | Crowned Hexagon |
| Head Height: | 0.141 Inches Nominal |
| Width Between Flats: | 0.428 Inches Minimum And 0.440 Inches Maximum |
| Hole Diameter: | 0.062 Inches Nominal |
| End Item Identification: | E Fwd Fuslag |
| Nominal Thread Diameter: | 0.250 Inches |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Features Provided: | Finished Head |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Flats |
| Part Name Assigned By Controlling Agency: | Bolt,machine,125,000 Psi-crowned Hexagon Head,adjusting |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unf |
| Specification/standard Data: | 80205-nas428 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428H4A7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.