

P/N NAS428H5A13

Description

Fastener Length: 1-7/16", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 1-13/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS428H5A13

Minimum Qty (MOQ): 5

NSN: 5306-00-638-4796

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







^{*} See page 2 for technical characteristics

P/N NAS428H5A13 Specifications

3a
Right-hand
1.313 Inches Minimum And 1.406 Inches Maximum
1.375 Inches Minimum And 1.437 Inches Maximum
Crowned Hexagon
0.172 Inches Nominal
0.490 Inches Minimum And 0.502 Inches Maximum
0.070 Inches Nominal
0.312 Inches
0.031 Inches Minimum And 0.062 Inches Maximum
1
Drilled
Finished Head
24
125000 Pounds Per Square Inch
26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hexagon Flats
Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall
Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall
Cadmium Overall And Chromate Overall
Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Unf
80205-nas428 Professional/industrial Association Standard

How to Order

