

Description

Fastener Length: 1-7/16", Hole Diameter: 1/16", Thread: 1/4-24, Thread Length: 1-13/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS428H5A13
Minimum Qty (MOQ):	5
NSN:	5306-00-638-4796
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS428H5A13 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.313 Inches Minimum And 1.406 Inches Maximum
Fastener Length:	1.375 Inches Minimum And 1.437 Inches Maximum
Head Style:	Crowned Hexagon
Head Height:	0.172 Inches Nominal
Width Between Flats:	0.490 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Nominal
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Material:	Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-s-6049 Mil Spec 1st Material Response Overall Or Mil-s-6050 Mil Spec 2nd Material Response Overall Or Mil-s-6098 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 4th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Or Mil-s-5626 Mil Spec 6th Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas428 Professional/industrial Association Standard

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428H5A13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.