

**Description**

Fastener Length: 1-7/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 1-13/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS428HK4A13                              |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5306-01-454-4377                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS428HK4A13 Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Thread Class:</b>                | 3a  |
| <b>Thread Direction:</b>            | Right-hand  |
| <b>Thread Length:</b>               | 1.313 Inches Minimum And 1.406 Inches Maximum   |
| <b>Fastener Length:</b>             | 1.375 Inches Minimum And 1.437 Inches Maximum   |
| <b>Head Style:</b>                  | Crowned Hexagon   |
| <b>Head Height:</b>                 | 0.141 Inches Nominal  |
| <b>Width Between Flats:</b>         | 0.428 Inches Minimum And 0.440 Inches Maximum   |
| <b>Hole Diameter:</b>               | 0.045 Inches Minimum And 0.050 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>     | 0.250 Inches  |
| <b>Grip Length:</b>                 | 0.062 Inches Minimum And 0.301 Inches Maximum   |
| <b>Hole Quantity:</b>               | 1   |
| <b>Hole Type:</b>                   | Drilled   |
| <b>Features Provided:</b>           | Finished Head   |
| <b>Thread Quantity Per Inch:</b>    | 28  |
| <b>Hardness Rating:</b>             | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall   |
| <b>Minimum Yield Strength:</b>      | 125000 Pounds Per Square Inch   |
| <b>Hole Configuration Style:</b>    | Hexagon Flats   |
| <b>Special Features:</b>            | Slotted Shank   |
| <b>Material:</b>                    | Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall |
| <b>Surface Treatment:</b>           | Cadmium Overall And Chromate Overall  |
| <b>Thread Series Designator:</b>    | Unf   |
| <b>Specification/standard Data:</b> | 80205-nas428 Professional/Industrial Association Standard   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428HK4A13> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.