

P/N NAS428HK4A14

Description

Fastener Length: 1-9/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 1-9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS428HK4A14

Minimum Qty (MOQ): 10 EA

NSN: 5306-01-493-9749

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS428HK4A14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.500 Inches Minimum And 1.562 Inches Maximum
Fastener Length:	1.500 Inches Minimum And 1.562 Inches Maximum
Head Style:	Hexagon
Head Height:	0.141 Inches Nominal
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.045 Inches Minimum And 0.050 Inches Maximum
Locking Feature:	Slotted Point
Grip Diameter:	0.2500 Inches Nominal
End Item Identification:	1520-01-125-5476
Nominal Thread Diameter:	0.2500 Inches
Hole Quantity:	2
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hole Configuration Style:	Hexagon Flats
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS428HK4A14 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.