

Description

Fastener Length: 2-", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 1-61/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS428HK4A20
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-530-2657
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS428HK4A20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.954 Inches Nominal
Fastener Length:	2.000 Inches Nominal
Head Style:	Crowned Hexagon
Head Height:	0.141 Inches Nominal
Width Between Flats:	0.438 Inches Nominal
Hole Diameter:	0.046 Inches Nominal
End Item Identification:	E Center Fuse
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Part Name Assigned By Controlling Agency:	Bolt,machine
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428HK4A20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.