

P/N NAS428HK4A20

Description

Fastener Length: 2-", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 1-61/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS428HK4A20

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-530-2657

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS428HK4A20 Specifications

hread Direction: Right-hand hread Length: 1.954 Inches Nominal astener Length: 2.000 Inches Nominal astener Length: Crowned Hexagon ead Style: Crowned Hexagon ead Helght: 0.141 Inches Nominal //dth Between Flats: 0.438 Inches Nominal //dth Between Flats: 0.450 Inches Minimum Ouerall And 32.0 Rockwell C Maximum Overall //dth Between Flats: 0.450 Inches Minimum Overall And 32.0 Rockwell C Maximum Overall //dth Between Flats: 0.450 Inches Minimum Overall And 32.0 Rockwell C Maximum Overall //dth Between Flats: 0.450 Inches Minimum Overall And 32.0 Rockwell C Maximum Overall Over		
hread Length: astener Length: astener Length: astener Length: astener Length: corowed Hexagon ead Style: corowed Hexagon lith Between Flats: astener Length: astener Length: astener Length: buildth Between Flats: astener Length: astener Flats: astener Length: astener Flats: as	Thread Class:	3a
aed Style: Crowned Hexagon ead Height: 0.431 Inches Nominal idith Between Flats: 0.438 Inches Nominal ole Diameter: 0.046 Inches Nominal ole Diameter: 0.046 Inches Nominal ole Diameter: 0.250 Inches ominal Thread Diameter: 0.250 Inches rip Length: 0.331 Inches Minimum And 0.062 Inches Maximum ole Quantity: 0.331 Inches Minimum And 0.062 Inches Maximum ole Quantity: 0.1 ole Type: Drilled ole Type: Drilled Inimum Tensile Strength: 0.2500 Pounds Per Square Inch ard Quantity Per Inch: 28 Illinimum Tensile Strength: 0.500 Pounds Per Square Inch ole Configuration Style: Hexagon Flats ard Name Assigned By Controlling gency: Alexandrian ard Name Assigned By Controlling ard Name Assigned By	Thread Direction:	Right-hand
ead Style: Crowned Hexagon ead Height: 0.141 Inches Nominal //idth Between Flats: 0.438 Inches Nominal ole Diameter: 0.466 Inches Nominal ole Diameter: 0.466 Inches Nominal ole Diameter: 0.450 Inches Nominal ole Quantification: 0.550 Inches rip Length: 0.931 Inches Minimum And 0.062 Inches Maximum ole Quantity: 0.931 Inches Minimum And 0.062 Inches Maximum ole Quantity: 0.931 Inches Minimum And 0.062 Inches Maximum ole Type: 0.931 Inches Minimum And 0.062 Inches Maximum ole Type: 0.931 Inches Minimum And 0.062 Inches Maximum ole Quantity Per Inch: 28 Illinimum Tensile Strength: 125000 Pounds Per Square Inch ardness Rating: 0.6.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall ole Configuration Style: Hexagon Flats ard Name Assigned By Controlling gency: 1416 Inches Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: urface Treatment: Cadmium Overall And Chromate Overall	Thread Length:	1.954 Inches Nominal
ead Height: 0.41 Inches Nominal //idth Between Flats: 0.438 Inches Nominal ole Diameter: 0.046 Inches Nominal ind Item Identification: E Center Fuse ominal Thread Diameter: 0.250 Inches rip Length: 0.031 Inches Minimum And 0.062 Inches Maximum ole Quantity: 1 ole Quantity: 1 ole Type: Drilled inimum Tensile Strength: 280 Pounds Per Square Inch ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall ole Configuration Style: Hexagon Flats art Name Assigned By Controlling gency: laterial: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: urface Treatment: Cadmium Overall And Chromate Overall	Fastener Length:	2.000 Inches Nominal
### Add the Between Flats: ### O. 0.438 Inches Nominal ### O. 0.46 Inches Nominal ### Identification: ### Identification: ### O. 0.250 Inches ### O. 0.250 Inches ### O. 0.250 Inches ### O. 0.250 Inches ### O. 0.31 Inches Minimum And 0.062 Inches Maximum ### Ole Quantity: ### Or Illed ### Or Illed ### Or Illed ### Identification: ### Or Illed	Head Style:	Crowned Hexagon
ole Diameter: on Item Identification: cominal Thread Diameter: ol. 250 Inches oninal Thread Diameter: ol. 250 Inches rip Length: ol. 0.31 Inches Minimum And 0.062 Inches Maximum ole Quantity: ole Quantity: ole Type: olic	Head Height:	0.141 Inches Nominal
In litem Identification: In litem Identificati	Width Between Flats:	0.438 Inches Nominal
ominal Thread Diameter: 0.250 Inches 0.031 Inches Minimum And 0.062 Inches Maximum ole Quantity: 1 ole Type: Drilled hread Quantity Per Inch: 28 Ilinimum Tensile Strength: 125000 Pounds Per Square Inch ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall ole Configuration Style: Hexagon Flats art Name Assigned By Controlling gency: laterial: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: urface Treatment: Cadmium Overall And Chromate Overall	Hole Diameter:	0.046 Inches Nominal
rip Length: 0.031 Inches Minimum And 0.062 Inches Maximum ole Quantity: 1 ole Type: Drilled hread Quantity Per Inch: 28 linimum Tensile Strength: 125000 Pounds Per Square Inch ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall ole Configuration Style: Hexagon Flats art Name Assigned By Controlling gency: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: Under Treatment: Cadmium Overall And Chromate Overall	End Item Identification:	E Center Fuse
ole Quantity: ole Type: Drilled hread Quantity Per Inch: linimum Tensile Strength: ardness Rating: ole Configuration Style: Hexagon Flats art Name Assigned By Controlling gency: laterial: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: urface Treatment: Cadmium Overall And Chromate Overall	Nominal Thread Diameter:	0.250 Inches
Drilled hread Quantity Per Inch: 28 linimum Tensile Strength: 125000 Pounds Per Square Inch ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall hexagon Flats art Name Assigned By Controlling gency: laterial: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: urface Treatment: Cadmium Overall And Chromate Overall	Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
hread Quantity Per Inch: Strength: 125000 Pounds Per Square Inch ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall ole Configuration Style: Hexagon Flats art Name Assigned By Controlling gency: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall daterial Document And lassification: Qq-p-416,ty 2,cl 3 Fed Spec Single Material Response Overall urface Treatment: Cadmium Overall And Chromate Overall	Hole Quantity:	1
Inimum Tensile Strength: ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall ole Configuration Style: Hexagon Flats Bolt,machine Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: urface Treatment: 125000 Pounds Per Square Inch 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall 40 Steel Comp Flats 41 Steel Comp Flats 42 Steel Comp 40 Steel Comp 41 Steel Comp 41 Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Steel Comp 41 Steel Comp 41 Steel Comp 8630 Overall Or Steel Comp 8740 Overall Or Steel Comp 41 Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Steel Comp 8740 Overall Or Steel Comp 41 Steel Comp 8740 Overall Or	Hole Type:	Drilled
ardness Rating: 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall ole Configuration Style: Hexagon Flats art Name Assigned By Controlling gency: Bolt,machine Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: Qq-p-416,ty 2,cl 3 Fed Spec Single Material Response Overall urface Treatment: Cadmium Overall And Chromate Overall	Thread Quantity Per Inch:	28
ole Configuration Style: art Name Assigned By Controlling gency: laterial: Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall laterial Document And lassification: urface Treatment: Hexagon Flats Bolt,machine Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Cadmium Overall And Chromate Overall	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Bolt,machine Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Interial Document And Inassification: Uniface Treatment: Cadmium Overall And Chromate Overall	Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall Interial Document And Ilassification: Urface Treatment: Cadmium Overall And Chromate Overall	Hole Configuration Style:	Hexagon Flats
Overall Or Steel Comp 4140 Overall Atterial Document And Iassification:	Part Name Assigned By Controlling Agency:	Bolt,machine
Qq-p-416,ty 2,cl 3 Fed Spec Single Material Response Overall urface Treatment: Cadmium Overall And Chromate Overall	Material:	
	Material Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Material Response Overall
hread Series Designator: Unf	Surface Treatment:	Cadmium Overall And Chromate Overall
	Thread Series Designator:	Unf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS428HK4A20 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.