

Description

Fastener Length: 2-", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 1-61/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS428HK4A20 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-530-2657 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS428HK4A20 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.954 Inches Nominal |
| Fastener Length: | 2.000 Inches Nominal |
| Head Style: | Crowned Hexagon |
| Head Height: | 0.141 Inches Nominal |
| Width Between Flats: | 0.438 Inches Nominal |
| Hole Diameter: | 0.046 Inches Nominal |
| End Item Identification: | E Center Fuse |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.031 Inches Minimum And 0.062 Inches Maximum |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Hardness Rating: | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall |
| Hole Configuration Style: | Hexagon Flats |
| Part Name Assigned By Controlling Agency: | Bolt,machine |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| Material Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428HK4A20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.