

P/N NAS428HK4A5

Description

Fastener Length: 5/8", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS428HK4A5

Minimum Qty (MOQ): 5 EA

NSN: 5306-00-720-8047

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS428HK4A5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.563 Inches Minimum And 0.594 Inches Maximum
Fastener Length:	0.625 Inches Nominal
Head Style:	Crowned Hexagon
Head Height:	0.141 Inches Nominal
Width Between Flats:	0.438 Inches Nominal
Hole Diameter:	0.046 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Flats
Special Features:	Supplied W/slot In End Of Shank
Material:	Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall
Material Document And Classification:	Mil-b-6812 Mil Spec All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS428HK4A5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.