

Description

Fastener Length: 13/16", Hole Diameter: 1/32", Thread: 1/4-28, Thread Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS428HK4A6
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-042-4389
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093460, Bolts / Nuts Noi Bbc / Zinc

NO IMAGE
AVAILABLE

P/N NAS428HK4A6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.678 Inches Minimum And 0.781 Inches Maximum
Fastener Length:	0.750 Inches Minimum And 0.812 Inches Maximum
Head Style:	Crowned Hexagon
Head Height:	0.131 Inches Minimum And 0.151 Inches Maximum
Width Between Flats:	0.428 Inches Minimum And 0.440 Inches Maximum
Hole Diameter:	0.035 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.031 Inches Minimum And 0.062 Inches Maximum
Hole Quantity:	1
Hole Type:	Drilled
Features Provided:	Finished Head
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Hardness Rating:	26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Longitudinal Hole
Special Features:	Slot In @thread End
Material:	Steel Comp 8740 Overall Or Steel Comp 4140 Overall Or Steel Comp 8735 Overall Or Steel Comp 4037 Overall Or Steel Comp 4130 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas428 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428HK4A6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.