

P/N NAS428K3A5

Description

Fastener Length: 1-", Thread: 10-32, Thread Length: 19/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS428K3A5
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-570-8366
Schedule B:	7318.15.8085
ECCN:	EAR99



^{*} See page 2 for technical characteristics

P/N NAS428K3A5 Specifications

Thread Direction: Right-hand O.594 Inches Maximum Fastener Length: 1.000 Inches Nominal Head Style: Crowned Hexagon Head Height: 0.109 Inches Nominal Width Between Flats: 0.373 Inches Minimum And 0.385 Inches Maximum O.190 Inches Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Historia Special Features: Slotted Shank Special Features: Slotted Shank Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Surface Treatment Document And Classification: Cadmium Overall Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:		
Thread Length: 0.594 Inches Maximum Fastener Length: 1.000 Inches Nominal Head Style: Crowned Hexagon Head Height: 0.109 Inches Nominal Width Between Flats: 0.373 Inches Minimum And 0.385 Inches Maximum Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Special Features: Slotted Shank Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6078 Mil Spec 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn std 5th Material Response Overall Surface Treatment: Cadmium Overall Ocadmium Overall Ocadmiu	Thread Class:	3a
Fastener Length: 1,000 Inches Nominal Head Style: Crowned Hexagon Head Height: 0.109 Inches Nominal Width Between Flats: 0.373 Inches Minimum And 0.385 Inches Maximum Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Special Features: Slotted Shank Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Surface Treatment: Cadmium Overall Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Thread Direction:	Right-hand
Head Style: Crowned Hexagon Head Height: 0.109 Inches Nominal Width Between Flats: 0.373 Inches Minimum And 0.385 Inches Maximum Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Special Features: Slotted Shank Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Steel Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3nd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall	Thread Length:	0.594 Inches Maximum
Head Height: 0.109 Inches Nominal Width Between Flats: 0.373 Inches Minimum And 0.385 Inches Maximum 0.190 Inches 32 Minimum Tensile Strength: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Special Features: Slotted Shank Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material: Material Document And Classification: Wil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Cadmium Overall Oq-p-416, Ty Ii, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Fastener Length:	1.000 Inches Nominal
Width Between Flats: 0.373 Inches Minimum And 0.385 Inches Maximum 0.190 Inches 7 Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Special Features: Slotted Shank Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Surface Treatment: Surface Treatment Document And Classification: Oq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Head Style:	Crowned Hexagon
Nominal Thread Diameter: 0.190 Inches Thread Quantity Per Inch: 32 Minimum Tensile Strength: 125000 Pounds Per Square Inch Special Features: Slotted Shank Material: Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall	Head Height:	0.109 Inches Nominal
Minimum Tensile Strength: Special Features: Material: Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Signature Strength: 32 125000 Pounds Per Square Inch 125000 Pounds Per Square Inch Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Cadmium Overall Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Width Between Flats:	0.373 Inches Minimum And 0.385 Inches Maximum
Minimum Tensile Strength: Special Features: Slotted Shank Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Surface Treatment Document And Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Nominal Thread Diameter:	0.190 Inches
Special Features: Material: Material: Material Document And Classification: Surface Treatment: Slotted Shank Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Or Steel Comp 4037 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Cadmium Overall Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Thread Quantity Per Inch:	32
Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 4130 Overall Or Steel Comp 4037 Overall Material Document And Classification: Surface Treatment: Surface Treatment Document And Classification: Steel Comp 4037 Overall Or Steel Comp 8740 Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Cadmium Overall Qq-p-416, Ty Ii, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material: Material Document And Classification: Steel Comp 4037 Overall Mil-s-5626 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Mil-s-6050 Mil Spec 3rd Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Cadmium Overall Surface Treatment Document And Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Special Features:	Slotted Shank
Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn Std 5th Material Response Overall Surface Treatment: Cadmium Overall Surface Treatment Document And Classification: Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Material:	
Surface Treatment Document And Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Material Document And Classification:	Response Overall Or Mil-s-6098 Mil Spec 4th Material Response Overall Or Mil-s-6758 Mil Spec 5th Material Response Overall Or Ams 6300 Assn
Document And Qq-p-416, Ty li, Cl 2 Fed Spec Single Treatment Response Overall Classification:	Surface Treatment:	Cadmium Overall
Thread Series Designator: Unjf	Surface Treatment Document And Classification:	Qq-p-416, Ty Ii, Cl 2 Fed Spec Single Treatment Response Overall
	Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/NAS428K3A5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.