

**Description**

Fastener Length: 2-1/4", Thread: 1/4-28, Thread Length: 2-7/32"

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS428K422                                |
| Minimum Qty (MOQ):      | 5 EA                                      |
| NSN:                    | 5306-00-977-9332                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS428K4-22 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 2.188 Inches Minimum And 2.219 Inches Maximum  |
| <b>Fastener Length:</b>                               | 2.250 Inches Nominal   |
| <b>Head Style:</b>                                    | Crowned Hexagon  |
| <b>Head Height:</b>                                   | 0.141 Inches Nominal   |
| <b>Width Between Flats:</b>                           | 0.438 Inches Nominal   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches   |
| <b>Grip Length:</b>                                   | 0.031 Inches Minimum And 0.062 Inches Maximum  |
| <b>Features Provided:</b>                             | Finished Head  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Minimum Tensile Strength:</b>                      | 125000 Pounds Per Square Inch  |
| <b>Hardness Rating:</b>                               | 26.0 Rockwell C Minimum Overall And 32.0 Rockwell C Maximum Overall  |
| <b>Special Features:</b>                              | Slot In Shank End  |
| <b>Material:</b>                                      | Steel Comp 4037 Overall Or Steel Comp 4130 Overall Or Steel Comp 8630 Overall Or Steel Comp 8735 Overall Or Steel Comp 8740 Overall Or Steel Comp 4140 Overall |
| <b>Material Document And Classification:</b>          | Mil-b-6812 Mil Spec All Material Responses Overall   |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,ty 2 Cl 3 Fed Spec Single Treatment Response Overall  |
| <b>Thread Series Designator:</b>                      | Unf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/NAS428K4-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.