

P/N NAS42DD6-24N

Description

NAS42DD6-24N Sleeve Spacer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS42DD624N

Minimum Qty (MOQ): 50

NSN: 5365-01-284-8146

ECCN: EAR99

National Motor Freight: 013120, Aluminum Article Noi Sub 6



^{*} See page 2 for technical characteristics

P/N NAS42DD6-24N Specifications

| Overall Length: | 0.3700 Inches Minimum And 0.3800 Inches Maximum |
|--|---|
| Body Outside Diameter: | 0.3650 Inches Minimum And 0.3850 Inches Maximum |
| Body Inside Diameter: | 0.1900 Inches Minimum And 0.1960 Inches Maximum |
| Corner Shape: | Square All Corners |
| Special Features: | Color Gray |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Ww-t-700/3,ty 1,t3 Fed Spec Single Material Response Overall Or Qq-a-225/6,t4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification | : Mil-a-8625,ty 1 Mil Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas42 Professional/industrial Association Standard |

How to Order

Order this sleeve spacer from our inventory online by visiting https://military-fasteners.com/spacers/sleeve+spacers/NAS42DD6-24N and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.