

Description

Hole Diameter: 3/16", Diameter: 3/8", Thickness: 1/32",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS42DD62FC
Minimum Qty (MOQ):	25
NSN:	5310-00-177-1144
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE
AVAILABLE

P/N NAS42DD6-2FC Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.190 Inches Minimum And 0.196 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Center Hole Shape Style:	Round
Thickness:	0.026 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.365 Inches Minimum And 0.385 Inches Maximum
Special Features:	Anodize Dyed Gray Oxide Film Dyed Blue
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3 Temper T3 Ty 1 Fed Spec Single Material Response Overall Or Qq-a-225/6 Temper T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Ty 1,cl 2 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Ty And Grade A/a,cl 1 Mil Spec 2nd Treatment Response Overall

How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS42DD6-2FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.