

**Description**

Hole Diameter: 3/16", Diameter: 3/8", Thickness: 1/32",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS42DD62FC
Minimum Qty (MOQ):	25
NSN:	5310-00-177-1144
Schedule B:	7616.10.3000
ECCN:	EAR99
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE  
AVAILABLE

## P/N NAS42DD6-2FC Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.190 Inches Minimum And 0.196 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Center Hole Shape Style:</b>	Round
<b>Thickness:</b>	0.026 Inches Minimum And 0.036 Inches Maximum
<b>Overall Diameter:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Special Features:</b>	Anodize Dyed Gray Oxide Film Dyed Blue
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Ww-t-700/3 Temper T3 Ty 1 Fed Spec Single Material Response Overall Or Qq-a-225/6 Temper T4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Ty 1,cl 2 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Ty And Grade A/a,cl 1 Mil Spec 2nd Treatment Response Overall

## How to Order

Order this flat washer from our inventory online by visiting <https://military-fasteners.com/washers/flat+washers/NAS42DD6-2FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.