

Description

Hole Diameter: 1/4", Diameter: 7/16", Thickness: 1/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS42DD82
Minimum Qty (MOQ):	30 EA
NSN:	5310-01-096-6983
Schedule B:	7609.00.0000
ECCN:	9A991
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE
AVAILABLE

P/N NAS42DD8-2 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.256 Inches Minimum And 0.263 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.026 Inches Minimum And 0.036 Inches Maximum
Overall Diameter:	0.428 Inches Minimum And 0.448 Inches Maximum
Color:	Gray Overall Or Blue Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3 Type 1 Temper T3 Fed Spec Single Material Response Overall Or Qq-a-225/6 Temper T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall Or Chromate Overall
Surface Treatment Document And Classification:	Mil-a-8625 Type 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
Specification/standard Data:	80205-nas42 Professional/industrial Association Standard

How to Order

Order this spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS42DD8-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.