



Military-Fasteners.com

P/N NAS42DD8-2

Description

Hole Diameter: 1/4", Diameter: 7/16", Thickness: 1/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | NAS42DD82 |
| Minimum Qty (MOQ): | 30 EA |
| NSN: | 5310-01-096-6983 |
| Schedule B: | 7609.00.0000 |
| ECCN: | 9A991 |
| National Motor Freight: | 194120, Washers / Gaskets / Pckg Dvcs Noi |



* See page 2 for technical characteristics

P/N NAS42DD8-2 Specifications

| | |
|------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.256 Inches Minimum And 0.263 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.026 Inches Minimum And 0.036 Inches Maximum |
| Overall Diameter: | 0.428 Inches Minimum And 0.448 Inches Maximum |
| Color: | Gray Overall Or Blue Overall |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Ww-t-700/3 Type 1 Temper T3 Fed Spec Single Material Response Overall Or Qq-a-225/6 Temper T4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall Or Chromate Overall |
| Surface Treatment Document And Classification: | Mil-a-8625 Type 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall |
| Specification/standard Data: | 80205-nas42 Professional/industrial Association Standard |

How to Order

Order this spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS42DD8-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.