

**Description**

Hole Diameter: 1/4", Diameter: 7/16", Thickness: 1/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS42DD82
Minimum Qty (MOQ):	30 EA
NSN:	5310-01-096-6983
Schedule B:	7609.00.0000
ECCN:	9A991
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE  
AVAILABLE

## P/N NAS42DD8-2 Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.256 Inches Minimum And 0.263 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.026 Inches Minimum And 0.036 Inches Maximum
<b>Overall Diameter:</b>	0.428 Inches Minimum And 0.448 Inches Maximum
<b>Color:</b>	Gray Overall Or Blue Overall
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Ww-t-700/3 Type 1 Temper T3 Fed Spec Single Material Response Overall Or Qq-a-225/6 Temper T4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall Or Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Type 1 Mil Spec 1st Treatment Response Overall Or Mil-c-5541 Mil Spec 2nd Treatment Response Overall
<b>Specification/standard Data:</b>	80205-nas42 Professional/industrial Association Standard

## How to Order

Order this spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS42DD8-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.