

P/N NAS42DD8-48FC

Description

Length: 3/4"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS42DD848FC

Minimum Qty (MOQ):

NSN: 5365-01-413-0713



P/N NAS42DD8-48FC Specifications

| Overall Length: | 0.7450 Inches Minimum And 0.7550 Inches Maximum |
|--|--|
| Body Outside Diameter: | 0.4280 Inches Minimum And 0.4480 Inches Maximum |
| Body Inside Diameter: | 0.2560 Inches Minimum And 0.2630 Inches Maximum |
| End Item Identification: | Pacer Dawn |
| Corner Shape: | Square All Corners |
| Special Features: | Tensile Strength 62,000 Psi Min.;finish Chemical Film Dyed Blue |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Ww-t-700/3, Type I, T3 Fed Spec Single Material Response Overall Or Qq-a-225/6, T4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Oxide Film Overall |
| Surface Treatment Document And Classification: | Mil-c-5541, Class 1a Mil Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |

How to Order

Order this sleeve spacer from our inventory online by visiting https://military-fasteners.com/spacers/sleeve+spacers/NAS42DD8-48FC and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/spacers/sleeve+spacers/NAS42DD8-48FC and selecting the quantity you