

**Description**

length: 5/8", size: #6, spacer, screw and bolt sleeve, aluminum with chemical film finish

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS43DD140FC
Minimum Qty (MOQ):	50
NSN:	5365-01-388-6256
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S



\* See page 2 for technical characteristics

## P/N NAS43DD1-40FC Specifications

<b>Overall Length:</b>	0.6200 Inches Minimum And 0.6300 Inches Maximum
<b>Body Outside Diameter:</b>	0.2400 Inches Minimum And 0.2600 Inches Maximum
<b>Body Inside Diameter:</b>	0.1430 Inches Minimum And 0.1720 Inches Maximum
<b>Corner Shape:</b>	Square All Corners
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Ww-t-700/3. Ty1 Fed Spec Single Material Response Overall Or Qq-a-226/6 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541, Cl 1a, Dyed Blue Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas43 Professional/industrial Association Standard

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD1-40FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.