

Description

NAS43DD1-64N Sleeve Spacer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|----------------------------|
| SKU / Model: | NAS43DD164N |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5365-01-358-2376 |
| ECCN: | EAR99 |
| National Motor Freight: | 115620, Bushings Noi I / S |

NO IMAGE
AVAILABLE

P/N NAS43DD1-64N Specifications

| | |
|---|--|
| Overall Length: | 0.9950 Inches Minimum And 1.0050 Inches Maximum |
| Body Outside Diameter: | 0.2400 Inches Minimum And 0.2600 Inches Maximum |
| Body Inside Diameter: | 0.1430 Inches Minimum And 0.1720 Inches Maximum |
| Corner Shape: | Square All Corners |
| Special Features: | Gray Anodize |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Ww-t-700/3,ty1,t3 Fed Spec Single Material Response Overall Or Qq-a-225/6,t4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty1 Mil Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas43 Professional/industrial Association Standard |

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD1-64N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.