

Description

NAS43DD3-124N Sleeve Spacer

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS43DD3124N
Minimum Qty (MOQ):	5
NSN:	5365-01-358-2276
Schedule B:	7616.99.5190
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS43DD3-124N Specifications

Overall Length:	1.9325 Inches Minimum And 1.9425 Inches Maximum
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
Corner Shape:	Square All Corners
Special Features:	Gray Anodize
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3,ty1,t3 Fed Spec Single Material Response Overall Or Qq-a-225/6,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty1 Mil Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas43 Professional/industrial Association Standard

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-124N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.