

Description

Screw and bolt sleeve spacer. Length: 2-1/4" use with screw or bolt size #2. 2024-T aluminum with chemical film.

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS43DD3144FC
Minimum Qty (MOQ):	10
NSN:	5365-01-361-2679
ECCN:	EAR99
National Motor Freight:	106940, Spacers / Separators I / S Noi Tubular

NO IMAGE
AVAILABLE

P/N NAS43DD3-144FC Specifications

Overall Length:	2.2450 Inches Minimum And 2.2550 Inches Maximum
Body Outside Diameter:	0.1780 Inches Minimum And 0.1980 Inches Maximum
Body Inside Diameter:	0.0970 Inches Minimum And 0.1020 Inches Maximum
Corner Shape:	Square All Corners
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-7000/3 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541 Mil Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas43 Professional/industrial Association Standard

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-144FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.