

## P/N NAS43DD3-24FC

### **Description**

length: 3/8" use with size: #8 or #10, screw and bolt sleeve, aluminum with chemical film finish, NAS43 series spacer

\* Manufacturer certifications are shipped with your order EREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS43DD324FC

Minimum Qty (MOQ): 50

NSN: 5365-01-330-7657

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 106940, Spacers / Separators I / S Noi Tubular









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS43DD3-24FC Specifications

Overall Length:	0.3700 Inches Minimum And 0.3800 Inches Maximum
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
Corner Shape:	Square All Corners
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3,ty 1,t3 Fed Spec Single Material Response Overall Or Qq-a-225/6,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges

## **How to Order**

Order this sleeve spacer from our inventory online by visiting <a href="https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-24FC">https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-24FC</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-24FC">https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-24FC</a> and selecting the quantity you