

**Description**

length: 1/2", use with size: #8 or #10, screw and bolt, anodized aluminum, NAS43DD3 series spacer

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS43DD332N
Minimum Qty (MOQ):	50
NSN:	5365-01-289-9753
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



\* See page 2 for technical characteristics

## P/N NAS43DD3-32N Specifications

<b>Overall Length:</b>	0.4950 Inches Minimum And 0.5050 Inches Maximum
<b>Body Outside Diameter:</b>	0.3020 Inches Minimum And 0.3220 Inches Maximum
<b>Body Inside Diameter:</b>	0.1940 Inches Minimum And 0.2340 Inches Maximum
<b>Corner Shape:</b>	Square All Corners
<b>Special Features:</b>	Color Gray
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Ww-t-700/3,t3 Ty1 Fed Spec Single Material Response Overall Or Qq-a-225/6 T4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Type 1 Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas43 Professional/Industrial Association Standard

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-32N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.