



Military-Fasteners.com

P/N NAS43DD3-43FC

Description

spacer - screw and bolt sleeve - aluminum with chemical film finish

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|----------------------------|
| SKU / Model: | NAS43DD343FC |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5365-01-353-6166 |
| National Motor Freight: | 115620, Bushings Noi I / S |



* See page 2 for technical characteristics

P/N NAS43DD3-43FC Specifications

| | |
|--|---|
| Overall Length: | 0.6670 Inches Minimum And 0.6770 Inches Maximum |
| Body Outside Diameter: | 0.3020 Inches Minimum And 0.3220 Inches Maximum |
| Body Inside Diameter: | 0.1940 Inches Minimum And 0.2340 Inches Maximum |
| Corner Shape: | Square All Corners |
| Material: | Aluminum Alloy 2024 Overall |
| Surface Treatment: | Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-43FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.