

**Description**

spacer - screw and bolt sleeve - aluminum with chemical film finish

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS43DD343FC
Minimum Qty (MOQ):	10
NSN:	5365-01-353-6166
National Motor Freight:	115620, Bushings Noi I / S



\* See page 2 for technical characteristics

# P/N NAS43DD3-43FC Specifications

Overall Length:	0.6670 Inches Minimum And 0.6770 Inches Maximum
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
Corner Shape:	Square All Corners
Material:	Aluminum Alloy 2024 Overall
Surface Treatment:	Chromate Overall
Surface Treatment Document And Classification:	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-43FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.