

Description

length: 45/64" use with screw or bolt size: #8 or #10, spacer, screw and bolt sleeve, anodized aluminum

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS43DD345N
Minimum Qty (MOQ):	25
NSN:	5365-01-410-7146
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S

NO IMAGE
AVAILABLE

P/N NAS43DD3-45N Specifications

Overall Length:	0.6981 Inches Minimum And 0.7081 Inches Maximum
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
Corner Shape:	Square All Corners
Special Features:	Gray Anodize
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3,ty1,t3 Fed Spec Single Material Response Overall Or Qq-a-225/6,t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty1 Mil Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas43 Professional/industrial Association Standard

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-45N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.