

# **P/N NAS43DD3-48N**

## **Description**

length: 3/4", size: #8 or #10, screw and bolt, anodized aluminum, NAS43 series spacer

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS43DD348N

Minimum Qty (MOQ): 50

NSN: 5365-01-296-9819

ECCN: EAR99

National Motor Freight: 013120, Aluminum Article Noi Sub 6









# P/N NAS43DD3-48N Specifications

Overall Length:	0.7450 Inches Minimum And 0.7550 Inches Maximum
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
Corner Shape:	Square All Corners
Special Features:	Color Gray
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3,t3 Ty1 Fed Spec Single Material Response Overall Or Qq-a-225/6 T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
<b>Surface Treatment Document And Classification</b>	: Mil-a-8625 Type 1 Mil Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas43 Professional/industrial Association Standard

## **How to Order**

Order this sleeve spacer from our inventory online by visiting <a href="https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-48N">https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-48N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.