

## P/N NAS43DD3-4N

### **Description**

length: 1/16" use with screw or bolt size: #8 or #10, spacer, screw and bolt sleeve, anodized aluminum

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS43DD34N

Minimum Qty (MOQ):

NSN: 5310-01-323-3701

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS43DD3-4N Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.194 Inches Minimum And 0.234 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.0575 Inches Minimum And 0.0675 Inches Maximum
Overall Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3,t3 Ty 1 Fed Spec Single Material Response Overall Or Qq-a-225/6 T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Type 1 Mil Spec Single Treatment Response Overall

## **How to Order**

Order this sleeve spacer from our inventory online by visiting <a href="https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-4N">https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-4N</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-4N">https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-4N</a> and selecting the quantity you