

Description

length: 1/16" use with screw or bolt size: #8 or #10, spacer, screw and bolt sleeve, anodized aluminum

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS43DD34N
Minimum Qty (MOQ):	10
NSN:	5310-01-323-3701
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS43DD3-4N Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.194 Inches Minimum And 0.234 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.0575 Inches Minimum And 0.0675 Inches Maximum
Overall Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-700/3,t3 Ty 1 Fed Spec Single Material Response Overall Or Qq-a-225/6 T4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Type 1 Mil Spec Single Treatment Response Overall

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-4N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.