

**Description**

length: 1/16" use with screw or bolt size: #8 or #10, spacer, screw and bolt sleeve, anodized aluminum

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS43DD34N
Minimum Qty (MOQ):	10
NSN:	5310-01-323-3701
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS43DD3-4N Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Hole Diameter:</b>	0.194 Inches Minimum And 0.234 Inches Maximum
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.0575 Inches Minimum And 0.0675 Inches Maximum
<b>Overall Diameter:</b>	0.302 Inches Minimum And 0.322 Inches Maximum
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Ww-t-700/3,t3 Ty 1 Fed Spec Single Material Response Overall Or Qq-a-225/6 T4 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625 Type 1 Mil Spec Single Treatment Response Overall

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-4N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.