

**Description**

length: 13/16

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS43DD352FC
Minimum Qty (MOQ):	25
NSN:	5365-01-358-0625
ECCN:	EAR99
National Motor Freight:	013120, Aluminum Article Noi Sub 6



## P/N NAS43DD3-52FC Specifications

<b>Overall Length:</b>	0.8075 Inches Minimum And 0.8175 Inches Maximum
<b>Body Outside Diameter:</b>	0.3020 Inches Minimum And 0.3220 Inches Maximum
<b>Body Inside Diameter:</b>	0.1940 Inches Minimum And 0.2340 Inches Maximum
<b>Corner Shape:</b>	Square All Corners
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Ww-t-700/3,ty 1,t3 Fed Spec Single Material Response Overall And Qq-a-225/6,ty1 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Mil-c-5541,cl 1a Mil Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas43 Professional/industrial Association Standard

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-52FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.