

**Description**

spacer, screw and bolt sleeve, aluminum with chemical film finish

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS43DD360FC
Minimum Qty (MOQ):	25
NSN:	5365-01-512-9941
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S

NO IMAGE  
AVAILABLE

## P/N NAS43DD3-60FC Specifications

<b>Overall Length:</b>	0.9325 Inches Minimum And 0.9425 Inches Maximum
<b>Body Outside Diameter:</b>	0.3020 Inches Minimum And 0.3220 Inches Maximum
<b>Body Inside Diameter:</b>	0.1940 Inches Minimum And 0.2340 Inches Maximum
<b>End Item Identification:</b>	Helicopter,utility.uh-60l; 1520-01-298-4532
<b>Special Features:</b>	Surface Finish Will Be Chemical Film Per Mil-c-5541,class 1a Dyed Blue.tensile Strength Is 62000 Psi Minimum. Use With Bolt Or Screw Diameter .164 And .190 Inch.
<b>Material:</b>	Aluminum Alloy Overall
<b>Material Document And Classification:</b>	Ww-t-700/3,type 1 Fed Spec Single Material Response Overall Or Qq-a-225/6 Assn Std Single Material Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-60FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.