

Description

spacer, screw and bolt sleeve, aluminum with chemical film finish

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS43DD360FC
Minimum Qty (MOQ):	25
NSN:	5365-01-512-9941
ECCN:	EAR99
National Motor Freight:	115620, Bushings Noi I / S

NO IMAGE
AVAILABLE

P/N NAS43DD3-60FC Specifications

Overall Length:	0.9325 Inches Minimum And 0.9425 Inches Maximum
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
End Item Identification:	Helicopter,utility.uh-60l; 1520-01-298-4532
Special Features:	Surface Finish Will Be Chemical Film Per Mil-c-5541,class 1a Dyed Blue.tensile Strength Is 62000 Psi Minimum. Use With Bolt Or Screw Diameter .164 And .190 Inch.
Material:	Aluminum Alloy Overall
Material Document And Classification:	Ww-t-700/3,type 1 Fed Spec Single Material Response Overall Or Qq-a-225/6 Assn Std Single Material Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-60FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.