

Description

length: 1-5/32", use with screw or bolt size: #8 or #10, spacer, screw and bolt sleeve, aluminum with chemical film finish

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS43DD374FC
Minimum Qty (MOQ):	25
NSN:	5365-01-558-4054
ECCN:	EAR99
National Motor Freight:	106940, Spacers / Separators I / S Noi Tubular

NO IMAGE
AVAILABLE

P/N NAS43DD3-74FC Specifications

Overall Length:	1.1562 Inches Nominal
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
Part Name Assigned By Controlling Agency:	Spacer, Sleeve-screw And Bolt
Special Features:	Screw Or Bolt Diameter 0.164 And 0.190
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ams-ww-t-700/3,ty1.t3 Fed Spec Single Material Response Overall Or Ams-qq-a-225/6.t4 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625.type 1 Mil Spec Single Treatment Response Overall
Style Designator:	17c-3 Solid, Plain, No Outside Flanges, Internal Flange At Both Ends
Specification/standard Data:	80205-nas43 Professional/industrial Association Standard

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-74FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.