

Description

length: 1-3/16" use with screw or bolt size: #8 or #10, spacer screw and bolt sleeve aluminum with chemical film finish

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|----------------------------|
| SKU / Model: | NAS43DD376FC |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5365-01-514-7461 |
| ECCN: | EAR99 |
| National Motor Freight: | 115620, Bushings Noi I / S |

NO IMAGE
AVAILABLE

P/N NAS43DD3-76FC Specifications

| | |
|---|--|
| Overall Length: | 1.1825 Inches Minimum And 1.1925 Inches Maximum |
| Body Outside Diameter: | 0.3020 Inches Minimum And 0.3220 Inches Maximum |
| Body Inside Diameter: | 0.1940 Inches Minimum And 0.2340 Inches Maximum |
| Corner Shape: | Square All Corners |
| Part Name Assigned By Controlling Agency: | Spacer,sleeve-screw Or Bolt |
| Special Features: | Screw Or Bolt Diameter 0.164 And 0.190 |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Mil-a-8625 Mil Spec Single Material Response Overall |
| Surface Treatment Document And Classification: | Mil-c-5541,class 1a,dyed Blue Mil Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-76FC> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.