



★ FASTENERS

Military-Fasteners.com

P/N NAS43DD3-80N

Description

Length: 1-1/4", size: #8 or #10, screw and bolt, anodized aluminum, NAS43 series spacer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | NAS43DD380N |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5365-01-300-3718 |
| ECCN: | EAR99 |
| National Motor Freight: | 106940, Spacers / Separators I / S Noi Tubular |



* See page 2 for technical characteristics

P/N NAS43DD3-80N Specifications

| | |
|--|---|
| Overall Length: | 1.2450 Inches Minimum And 1.2550 Inches Maximum |
| Body Outside Diameter: | 0.3020 Inches Minimum And 0.3220 Inches Maximum |
| Body Inside Diameter: | 0.1940 Inches Minimum And 0.2340 Inches Maximum |
| Corner Shape: | Square All Corners |
| Special Features: | Anodize Gray |
| Material: | Aluminum Alloy 2024 Overall |
| Material Document And Classification: | Ww-t-700/3,ty 1,t3 Fed Spec Single Material Response Overall Or Qq-a-225/6,t4 Fed Spec Single Material Response Overall |
| Surface Treatment: | Anodize Overall |
| Surface Treatment Document And Classification: | Mil-a-8625,ty 1 Mil Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas43 Professional/industrial Association Standard |

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-80N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.