

Description

length: 1/8, for size: #8 or #10, screw or bolt sleeve, anodized aluminum, NAS43 series spacer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|------------------------------------|
| SKU / Model: | NAS43DD38N |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5365-00-722-5839 |
| Schedule B: | 7609.00.0000 |
| ECCN: | EAR99 |
| National Motor Freight: | 013120, Aluminum Article Noi Sub 6 |



* See page 2 for technical characteristics

P/N NAS43DD3-8N Specifications

| | |
|---|--|
| Overall Length: | 0.1250 Inches Nominal |
| Body Outside Diameter: | 0.3020 Inches Minimum And 0.3220 Inches Maximum |
| Body Inside Diameter: | 0.1940 Inches Minimum And 0.2340 Inches Maximum |
| Corner Shape: | Square All Corners |
| Special Features: | Fleet Ballistic Missile Quality As Identified By Quality Control No. Poso 911950 |
| Material: | Aluminum Alloy Overall |
| Surface Treatment: | Anodize Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas43 Professional/industrial Association Standard |
| Departure From Cited Designator: | As Modified By Features |

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD3-8N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.