

**Description**

NAS43 series spacer

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS43DD64N
Minimum Qty (MOQ):	100
NSN:	5310-01-025-1902
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N NAS43DD6-4N Specifications

<b>Cross-sectional Shape Style:</b>	Rectangular
<b>Peripheral Shape Style:</b>	Round
<b>Center Hole Shape Style:</b>	1 Round
<b>Thickness:</b>	0.057 Inches Minimum And 0.067 Inches Maximum
<b>Overall Diameter:</b>	0.485 Inches Minimum And 0.515 Inches Maximum
<b>Minimum Tensile Strength:</b>	62000 Pounds Per Square Inch
<b>Special Features:</b>	Diameter 0.377 In. Min,0.427 In. Max
<b>Material:</b>	Aluminum Alloy 2024 Overall
<b>Material Document And Classification:</b>	Ww-t-785,t3,ty 1 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Anodize Overall
<b>Surface Treatment Document And Classification:</b>	Mil-a-8625,ty 1 Mil Spec Single Treatment Response Overall

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD6-4N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.