



Military-Fasteners.com

P/N NAS43DD6-4N

Description

NAS43 series spacer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS43DD64N
Minimum Qty (MOQ):	100
NSN:	5310-01-025-1902
Schedule B:	7616.10.9090
ECCN:	9A991
National Motor Freight:	194120, Washers / Gaskets / Pckg Dvcs Noi



* See page 2 for technical characteristics

P/N NAS43DD6-4N Specifications

Cross-sectional Shape Style:	Rectangular
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.067 Inches Maximum
Overall Diameter:	0.485 Inches Minimum And 0.515 Inches Maximum
Minimum Tensile Strength:	62000 Pounds Per Square Inch
Special Features:	Diameter 0.377 In. Min,0.427 In. Max
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Ww-t-785,t3,ty 1 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625,ty 1 Mil Spec Single Treatment Response Overall

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43DD6-4N> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.