

P/N NAS43HT3-10

Description

length: 5/32", size: #8 or #10, spacer, screw and bolt sleeve, cadmium plated alloy steel, NAS43 series spacer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS43HT310

Minimum Qty (MOQ): 25

NSN: 5365-00-541-9955

Schedule B: 7326.90.

ECCN: EAR99

National Motor Freight: 106940, Spacers / Separators I / S Noi Tubular









^{*} See page 2 for technical characteristics

P/N NAS43HT3-10 Specifications

Overall Length:	0.1510 Inches Minimum And 0.1610 Inches Maximum
Body Outside Diameter:	0.3020 Inches Minimum And 0.3220 Inches Maximum
Body Inside Diameter:	0.1940 Inches Minimum And 0.2340 Inches Maximum
Corner Shape:	Square All Corners
Material:	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
Material Document And Classification:	Mil-t-6736,ty 1,cond Ht-125 Mil Spec 1st Material Response Overall Or Ams 6530 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Style Designator:	17c Solid, Plain, No Outside Flanges
Style Designator:	Solid, Plain, No Outside Flanges
Specification/standard Data:	80205-nas43 Professional/industrial Association Standard

How to Order

Order this sleeve spacer from our inventory online by visiting https://military-fasteners.com/spacers/sleeve+spacers/NAS43HT3-10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.