

Description

length: 1/2 use with screw or bolt size: #8 or #10, spacer, screw and bolt sleeve, cadmium plated alloy steel, NAS43 series spacer

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--|
| SKU / Model: | NAS43HT332 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5365-00-661-8793 |
| Schedule B: | 7318.90.8595 |
| ECCN: | EAR99 |
| National Motor Freight: | 106940, Spacers / Separators I / S Noi Tubular |



* See page 2 for technical characteristics

P/N NAS43HT3-32 Specifications

| | |
|---|--|
| Overall Length: | 0.4950 Inches Minimum And 0.5050 Inches Maximum |
| Body Outside Diameter: | 0.3020 Inches Minimum And 0.3220 Inches Maximum |
| Body Inside Diameter: | 0.1940 Inches Minimum And 0.2340 Inches Maximum |
| Corner Shape: | Square All Corners |
| Special Features: | Color Bronze |
| Material: | Steel Comp 4130 Overall Or Steel Comp 8630 Overall |
| Material Document And Classification: | Mil-t-6736,ty 1,cond Ht-125 Mil Spec 1st Material Response Overall Or Mil-t-6732,ty 1,cond Ht-125 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Style Designator: | 17c Solid, Plain, No Outside Flanges |
| Style Designator: | Solid, Plain, No Outside Flanges |
| Specification/standard Data: | 80205-nas43 Professional/industrial Association Standard |

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43HT3-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.