

Description

length: 1/16", size: #8 or #10, screw and bolt sleeve, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS43HT34
Minimum Qty (MOQ):	25
NSN:	5310-00-826-2479
ECCN:	EAR99
National Motor Freight:	194160, Washer Or Gaskets, Iron Or Steel,



P/N NAS43HT3-4 Specifications

Cross-sectional Shape Style:	Rectangular
Hole Diameter:	0.194 Inches Minimum And 0.234 Inches Maximum
Peripheral Shape Style:	Round
Center Hole Shape Style:	1 Round
Thickness:	0.057 Inches Minimum And 0.067 Inches Maximum
Overall Diameter:	0.302 Inches Minimum And 0.322 Inches Maximum
Minimum Tensile Strength:	125000 Pounds Per Square Inch
Material:	Steel Comp 4130 Overall
Material Document And Classification:	Mil-t-6736 Ty 1,cond N Or Ht Mil Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Specification/standard Data:	80205-nas43 Professional/industrial Association Standard

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43HT3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.