

Description

length: 1/16", size: #8 or #10, screw and bolt sleeve, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS43HT34 |
| Minimum Qty (MOQ): | 25 |
| NSN: | 5310-00-826-2479 |
| ECCN: | EAR99 |
| National Motor Freight: | 194160, Washer Or Gaskets, Iron Or Steel, |



* See page 2 for technical characteristics

P/N NAS43HT3-4 Specifications

| | |
|--|--|
| Cross-sectional Shape Style: | Rectangular |
| Hole Diameter: | 0.194 Inches Minimum And 0.234 Inches Maximum |
| Peripheral Shape Style: | Round |
| Center Hole Shape Style: | 1 Round |
| Thickness: | 0.057 Inches Minimum And 0.067 Inches Maximum |
| Overall Diameter: | 0.302 Inches Minimum And 0.322 Inches Maximum |
| Minimum Tensile Strength: | 125000 Pounds Per Square Inch |
| Material: | Steel Comp 4130 Overall |
| Material Document And Classification: | Mil-t-6736 Ty 1,cond N Or Ht Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Specification/standard Data: | 80205-nas43 Professional/industrial Association Standard |

How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43HT3-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.