

## Description

length: 3/8" use with screw or bolt size: #8 or #10, spacer, screw and bolt sleeve, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS43HT424
Minimum Qty (MOQ):	25
NSN:	5365-00-300-4379
ECCN:	EAR99
National Motor Freight:	106940, Spacers / Separators I / S Noi Tubular



\* See page 2 for technical characteristics

## P/N NAS43HT4-24 Specifications

<b>Overall Length:</b>	0.3700 Inches Minimum And 0.3800 Inches Maximum
<b>Body Outside Diameter:</b>	0.3650 Inches Minimum And 0.3850 Inches Maximum
<b>Body Inside Diameter:</b>	0.2560 Inches Minimum And 0.2970 Inches Maximum
<b>Corner Shape:</b>	Square All Corners
<b>Special Features:</b>	Color Iridescent Bronze
<b>Material:</b>	Steel Comp 4130 Overall Or Steel Comp 8630 Overall
<b>Material Document And Classification:</b>	Mil-t-6736,type 1,condition Ht125 Mil Spec 1st Material Response Overall Or Ams 6530 Assn Std 2nd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Style Designator:</b>	17c Solid, Plain, No Outside Flanges
<b>Style Designator:</b>	Solid, Plain, No Outside Flanges
<b>Specification/standard Data:</b>	80205-nas43 Professional/industrial Association Standard

## How to Order

Order this sleeve spacer from our inventory online by visiting <https://military-fasteners.com/spacers/sleeve+spacers/NAS43HT4-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.