

Description

Fastener Length: 45/64", Thread: 8-32, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS44026
Minimum Qty (MOQ):	80 EA
NSN:	5305-01-264-3206
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS4402-6 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.223 Inches Nominal
Fastener Length:	0.673 Inches Minimum And 0.703 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.331 Inches Nominal
Head Height:	0.072 Inches Nominal
Grip Diameter:	0.1621 Inches Minimum And 0.1627 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.164 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Assn Std Single Material Response Overall Or Mil-s-6049 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416a,ty 11,cl 3 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjc
Specification/standard Data:	80205-nas4402-6 Professional/industrial Association Specification

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4402-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.