

**Description**

Fastener Length: 45/64", Thread: 8-32, Thread Length: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS44026
Minimum Qty (MOQ):	80 EA
NSN:	5305-01-264-3206
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS4402-6 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.223 Inches Nominal
<b>Fastener Length:</b>	0.673 Inches Minimum And 0.703 Inches Maximum
<b>Head Style:</b>	Pan No. 2
<b>Head Diameter:</b>	0.331 Inches Nominal
<b>Head Height:</b>	0.072 Inches Nominal
<b>Grip Diameter:</b>	0.1621 Inches Minimum And 0.1627 Inches Maximum
<b>Single Shear Strength:</b>	95000 Pounds Per Square Inch
<b>Internal Drive Style:</b>	Tri-wing Recess
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Grip Length:</b>	0.365 Inches Minimum And 0.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Mil-s-5000 Assn Std Single Material Response Overall Or Mil-s-6049 Assn Std Single Material Response Overall Or Ams6322 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416a,ty 11,cl 3 Assn Std Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjc
<b>Specification/standard Data:</b>	80205-nas4402-6 Professional/industrial Association Specification

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4402-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.