

Description

length: 1.011", grip: 0.688", thread: 10-32, 100°, close tolerance bolt - reduced head short thread - cadmium plated alloy steel - tri-slot recess"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS440311
Minimum Qty (MOQ):	10
NSN:	5305-01-219-8056



* See page 2 for technical characteristics

P/N NAS4403-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.323 Inches Nominal
Fastener Length:	0.996 Inches Minimum And 1.026 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.338 Inches Nominal
Internal Drive Style:	Tri-wing Recess
Nominal Thread Diameter:	0.1900 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 4340 Or Steel Comp 8740
Screw Surface Treatment:	Cadmium
Screw Surface Treatment Document And Classification:	Qq-p-416a Ty2 Cl3 Fed Spec Single Treatment Response
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas4403 Professional/industrial Association Standard

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4403-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.