

Description

length: 1.198", grip: 0.875", thread: 10-32, 100°, close tolerance bolt - reduced head short thread - cadmium plated alloy steel - tri-slot recess"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS440314 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-261-1905 |



P/N NAS4403-14 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.308 Inches Minimum And 0.338 Inches Maximum |
| Fastener Length: | 1.183 Inches Minimum And 1.213 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.338 Inches Minimum And 0.381 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Internal Drive Style: | Tri-wing Recess |
| Nominal Thread Diameter: | 0.1900 Inches |
| Grip Length: | 0.865 Inches Minimum And 0.885 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall And Mil-s-6049 Mil Spec 2nd Material Response Overall And Ams6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl 3 Fed Spec 1st Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas4403 Professional/industrial Association Standard |

How to Order

Order this close tolerance screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/NAS4403-14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.